Sure-Trac Implement Trailers

The frame is heavy duty structural C-channel with 3 inch channel cross members. The attention to detail in design and construction is unmatched with features like stake pockets & rub rail, sealed recessed lights, side steps, and a full frame wrap tongue. It all adds up to the best implement trailer value you can find.

IMPLEMENT SPECIFICATIONS		
		14K
GVWR (Lbs)		14000
GAWR (Lbs/Axle)		7000
		2750
18 ft.		3050
18 ft.		11050
		10850
Max Hitch Wt.		1400
Frame		6 Inch C-Channel
Cross Members		3 Inch C-Channel (16 On-Ctr)
Tongue		6 Inch C-Channel
Coupler	2 5/16 A-Frame	
Jack	Coupler Mounted Jack	
Fenders	HD Tread Plate	
Axles	Easy Lube Cambered Brake	
Suspension	Eye to Eye Spring	
Tires		235/80*16
		(R) Radial
		LRE
Wheel Size		16 x 6K, 8 Lug on 6.5
Wheels	White or Grey, Modular	
Floor	2 x 6 Treated Pine	
Lights	Rubber Mounted /Sealed DOT stop, Tail, Turn, Marking and Clearance.	
Electric Plug	7 Way Round	
Finish	Powdered Coated High Gloss	
Overall Length 16 ft.	21â€™ 9â€	
18 ft.	23â€™ 9â€	
20 ft.	25â€™ 9â€	
Flat Length 16 ft.	14'	
18 ft.	16'	
20 ft.	18'	
Drop-Tail Length	26"	
Bed Width	81-1/4â€	
Floor Height	24"	
Coupler Height		20â€
Ramps	3â€ C-Channel	
OPTIONS		