

2015 Specifications For: Implement

Standard Features

Â·(4) 5K D-Ring Tie Downs	Â·Sealed LED Lights
Â·Eye To Eye Spring Axle	Â·Pressure Treated 2 x 6 Decking
Â·Powder Coat Finish	Â·C-Channel Full Wrap Tongue
Â·5' Stand Up Ramps	Â·HD Reinforced Diamond Plate Fenders
Â·Easy Lube Hubs	Â·Rear Board Retainers
Â·Coupler Mounted Jack	Â·Stake Pockets and Rub Rail
Â·Sealed Brake Connections	Â·Bead Blasted, Iron Phosphate Washed
Â·Spare Tire Mount	Â·Sealed Wire Harness
Â·Spring Assisted Ramps	

	14K
GVWR (lbs)	14,000
GAWR (lbs)	7,000
Curb Weight (lbs)	2,870
Payload (lbs)	11,130
Frame	6" C-Channel
Cross Members	3" C-Ch, 16" On-Ctr
Tongue	6" C-Channel
Coupler	2-5/16 A-Frame
Jack	Zinc Plated Set-Back Jack
Fenders	HD Tread Plate
EZ Lube Axles	Easy Lube Cambered Brake
Suspension	Eye to Eye Spring
Tires	235/80R16
Wheels	16 in, 8 on 6.5
	White Spoke
Decking	2 x 6 Treated Pine
Lights	Sealed LED Lights
Electric Plug	7 Way Round
Finish	Powder Coated High Gloss Black
Length Overall/Flat	23'9"/16'
Drop-Tail Length	26"
Bed Width	81-1/4"
Deck Height	24"
Coupler Height	20"
Ramps	3" C-Channel, Stand Up, Spring Assisted