

2015 Specifications For: Angle Iron

Standard Features

- Fold Flat Gate
- 2x6 Pressure Treated Deck
- Powder Coat Finish
- Easy Lube Hubs
- Zinc Plated Coupler Mounted Jack
- DOT Approved Lighting
- Bead Blasted, Iron Phosphate Washed
- Self-Retained Gate Pins
- Jeep® Style Fenders (with Backers)
- Gel Filled Electrical Connectors
- Board Retainers Front and Back
- Radial Tires

	5 x 8, 3k
GVWR (Lbs.)	2,990
GAWR (Lbs./Axle)	3,500
Curb Weight	590
Payload	2,400
Frame	3 x 2 x 3/16
Cross Members	3 x 2 x 3/16 (24" On Center)
Top Rail	2 x 2 x 1/8 Angle
Tongue	A-Frame 3" Channel
Uprights	2 x 2 x 1/8 Angle
Coupler	2" Ball
Jack	Zinc Plated Coupler Mounted Jack
Fenders	Square Rolled with Back
EZ Lube Axles	Cambered Idler with Brake Flange
Suspension	Leaf Spring
Tires	205/75R 15 LRC
Wheels	15 in. 5 on 4.5
	White Spoke
Decking	2 x 6 Pressure Treated Pine
Lights	DOT Stop, Turn, Tail, Marking and Clearance
Electric Plug	4 Way Flat
Finish	Powder Coated High Gloss Black
Overall Length	137"
Bed Length	96"
Bed Width	61.5"
Deck Height	18"
Coupler Height	16"
Gate	2 x 2 Tube, Mesh Covered, Full Width Ramp Gate