

2015 Specifications For: Implement

Standard Features

- (4) 5K D-Ring Tie Downs
- Eye To Eye Spring Axle
- Powder Coat Finish
- 5' Stand Up Ramps
- Easy Lube Hubs
- Coupler Mounted Jack
- Sealed Brake Connections
- Spare Tire Mount
- Spring Assisted Ramps
- Sealed LED Lights
- Pressure Treated 2 x 6 Decking
- C-Channel Full Wrap Tongue
- HD Reinforced Diamond Plate
- Fenders
- Rear Board Retainers
- Stake Pockets and Rub Rail
- Bead Blasted, Iron Phosphate Washed
- Sealed Wire Harness

	14K
GVWR	14,000 #
GAWR	7,000 #
Curb Weight	2,870 #
Payload	11,130 #
Frame	6" C-Channel
Cross Members	3" C-Ch, 16" On-Ctr
Tongue	6" C-Channel
Coupler	2-5/16 A-Frame
Jack	Zinc Plated Set-Back Jack
Fenders	HD Tread Plate
EZ Lube Axles	Easy Lube Cambered Brake
Suspension	Eye to Eye Spring
Tires	235/80R16
Wheels	16 in, 8 on 6.5
	White Spoke
Decking	2 x 6 Treated Pine
Lights	Sealed LED Lights
Electric Plug	7 Way Round
Finish	Powder Coated High Gloss Black
Length Overall/Flat -18	23'9"/16'
Drop-Tail Length	26â€
Bed Width	81-1/4â€
Deck Height	24"
Coupler Height	20"
Ramps	3" C-Channel, Stand Up, Spring Assisted