



110 East North Avenue, Carol Stream, IL 60188 Toll Free 800-832-5331 ph. (630) 580-5840 fx (630) 580-5843

2017 MTI 8.5' Wide Round Top Cargo Trailer

| Model | Description |
|-----------|--|
| 8.5X16TA2 | 8.5 x 16 TA2 MST (Spring Axle) Exterior Color: White |

| SELECTED OPTIONS | | | |
|------------------|--|-----------------|----------|
| Option Code | Description | Unit of Measure | Quantity |
| 2.01 | Upgrade to Gray Mod Rims -- In Place of White Mod Rims | ea. | 4 |
| 4.21 | Radial Tires -- In Place of Bias Only | ea. | 4 |
| 5.14 | 3rd Member Tongue with 12" Extension | ea. | 1 |
| 6.09 | Stabilizer Jacks (Light Duty) 650 lb. - Flip Up | pr. | 1 |
| 6.24 | Crossmembers - Additional for 16" On Center | ea. | 4 |
| 6.39 | Upgrade to 1" x 1.5" Tube Walls | ft. | 16 |
| 7.14 | Rope Tie, Light Duty Surface Mounted | ea. | 6 |
| 7.50 | 3/8" Plywood Walls In Place of Luan | Unit | 1 |
| 2.02 | Add 3/4" Plywood Kick Panels | ft. | 16 |
| 12.01 | Wall Switch | ea. | 1 |
| 12.21 | LED 4 3/4" Oval Shaped, Surface Mounted, Interior Dome Light | ea. | 2 |
| 15.35 | Salem Sidewall Vent | ea. | 2 |
| 15.45 | Screwless Sides | ft. | 16 |
| 14.54 | Metal Door Holdbacks In Place Of Plastic | ea. | 1 |
| 14.11 | Ramp Door With Flap for 8/8.5 Wide - Std. Height | ea. | 1 |

Selected Rear Door Standard Duty Ramp



MIDDLEBURY TRAILERS

MST Series

5', 6', & 7' Wides
Round Top
Cargo Trailer



MST Shown with Options:
Two-Tone Metal
Brite Aluminum Corners

STANDARD FEATURES & SPECIFICATIONS

Hitch

2-5/16" Coupler with Safety Chains - Tandem Axles
2,000 lb. Top Wind Jack w/Sand Pad

Axle

MST = Spring Axles

Brake Axles on SAE and Tandem Axle Models

Tires and Rims

"D" = Bias-Ply Tires, "R" = Radial Tires

MST

| | | |
|----------------|-------------|-------------|
| 3,000 lb. Axle | ST205/75D15 | |
| 3,500 lb. Axle | ST205/75D15 | ST205/75R15 |
| 5,200 lb. Axle | ST225/75R15 | |

White Wheels Standard on MST and MTT Models

Frame

All Frames are Undercoated

| | Floor | Walls | Roof |
|------------------------|----------|----------|----------|
| MST 5', 6', & 7' Wides | 24" o.c. | 24" o.c. | 24" o.c. |
| All 8.5' Wides | 24" o.c. | 16" o.c. | 24" o.c. |
| All TA3 Axles | 16" o.c. | 16" o.c. | 24" o.c. |

Side Door

8.5' Wide, 12' to 16' -- 36" Camlock Door & No Step*

Rear Doors

| Width | Single Door | Double Door | Ramp Door |
|-------|-------------|-------------|------------|
| 5' | X | X | Light Duty |
| 6' | | X | Light Duty |
| 7' | | X | Light Duty |
| 8.5' | | X | |

* Light Duty Ramp Door has a 1,000 lb. capacity

Interior

3/4" Engineered Wood Flooring
MST - Lauan Walls, Trimmed with Lauan

Interior Heights

8.5' Wides - 6' 6"

Exterior

.030 Exterior Metal
Fiberglass Cap
24" ATP Stoneguard
Galvanized Steel Roof
Aluminum Fenders

3" Lower Trim

Electrical

Breakaway Box, Battery, & Switch On Electric Brake Axles
(2) 12-Volt Dome Lights With Switch
7-Way Plug on Electric Brake Axles
4-Way Plug on Idler Axles
LED Strip Tail Light/Brake Lights, Surface Mounted
LED Surface Mounted Clearance Lights