





ADVANTAGE TRAILERS AND HITCHES

110 E. North Ave.
 Carol Stream, IL 60188
 888-280-6695
www.advantagetrailer.com

MODEL INFO

Configured Model #: QSTSB7014+0-2T5.2K

Quest Steel Trailer

7'W x 14'L x 7.5'H, (2) 5200# Torsion Axle(s)

VIN: ...HE208291

Warranty: 5 YR STR, 3 YR LTD, 1 YR ELEC WARRANTY

COLOR: Polar White (Standard)

REAR COLOR: None

COLOR - CABINETS: Polar White

SPECIFICATIONS

Part Name	Qty	UOM	Ref.
BASE MODEL			
QSTSB7014+0-2T5.2K	1	ea	OPT
FRAME			
AXLE - 5200# - TORSION - EZ LUBE HUBS - ELECTRIC BRAKES GROUND CLEARANCE: STANDARD (APPROX. 14.25" - NO LOAD)	2	ea	STD
AXLE SPACING - NO SPREAD	1	ea	STD
ALL TUBE WALL CONSTRUCTION	14	ft	STD
COUPLER - A-FRAME - 2-5/16" - 10,000#	1	ea	STD
CROSS MEMBERS - FLOOR - 16" O/C	14	ft	OPT
CROSS MEMBERS - ROOF - 16" O/C - 1" X 2"	14	ft	STD
CROSS MEMBERS - WALL - CS - 16" O/C - 1" X 1.5"	14	ft	STD
CROSS MEMBERS - WALL - RS - 16" O/C - 1" X 1.5"	14	ft	STD
FLOOR DESIGN - FLAT	1	ea	STD
FRAME - 5"	14	ft	STD
FRAME - FULL PERIMETER - STEEL - PAINTED	14	ft	STD
FRAME PROTECTION - SKID PLATES	1	pr	STD
FRONT DESIGN - FLAT	1	ea	STD
JACK - TONGUE - TOP WIND - 5000# - ZINC	1	ea	STD
JACK - STABILIZER - SCISSOR - 24" - 5000# Location: FRONT & REAR	2	pr	OPT
TIRE/WHEEL - ST225/75R15/LRE - RADIAL ON GREY MOD	4	ea	STD
SPARE TIRE/WHEEL - ST225/75R15/LRE - RADIAL ON GREY MOD	1	ea	OPT
SPARE TIRE MOUNT - EXTERIOR WALL - 6 LUG	1	ea	OPT

TONGUE - STANDARD	1 ea	STD
TRUCK PLUG - 7 WAY - BUMPER PULL	1 ea	STD
BACKER - ST - 12 GA - FLOOR	12 sq	OPT
BACKER - ST - 12 GA - WALL	17 sq	OPT
EXTERIOR		
EXTERIOR ALUMINUM - STANDARD COLOR • Color: Polar White (Standard)	14 ft	STD
EXTERIOR FASTENER - SCREWLESS	14 ft	STD
EXTERIOR ALUMINUM THICKNESS - .030	14 ft	STD
FENDERS - AL	2 ea	STD
GRAVEL GUARD - ATP - 24" - WITH J RAIL	1 ea	STD
ROOF - ONE PIECE - ALUMINUM	14 ft	STD
TRIM - VERTICALS - FRONT - COLOR MATCHED	1 ea	STD
TRIM - HEADER - REAR - COLOR MATCHED	1 ea	STD
TRIM - VERTICALS - REAR - COLOR MATCHED	1 ea	STD
TRIM - RUB RAIL - UPPER - ALUMINUM - 3"	14 ft	STD
TRIM - RUB RAIL - LOWER - ALUMINUM - 3"	14 ft	STD
VENT - ROOF - MANUAL - 14"	1 ea	OPT
DOORS		
TRANSITION FLAP - TPO - BLACK COIN - 16"L	1 ea	STD
RAMP DOOR FLOORING - REAR - TPO - BLACK COIN	1 ea	OPT
DOOR ACCESSORIES - ALUMINUM BAR LOCK FOR RAMP OR STAGE DOOR	1 pr	OPT
HASP - STAINLESS STEEL - FOR CAM BARS/BAR LOCKS ON RAMP DOOR	1 pr	OPT
DOOR - ENTRANCE - 405 SERIES - 36" X 78" - FLUSH LOCK • RIGHT HINGE	1 ea	OPT
STEP - SLIDE IN/OUT -ALUMINUM - 36"	1 ea	OPT
DOOR - ACCESS - 405 SERIES - 8" X 8" - W/ BRISTLES • LEFT HINGE	1 ea	OPT
INTERIOR		
INTERIOR HEIGHT - 7.5'	14 ft	OPT
CABINET - ALUMINUM - UPPER - STRAIGHT - FULL WIDTH - W/ RADIUS LOWER EDGE - TOP HINGED DOORS AND GAS SHOCKS • Cabinet Color: Polar White • LOCATION: FRONT WALL	1 ea	OPT
INTERIOR CEILING - WHITE VINYL • Cove Color: Polar White • Spring Box Color: Polar White	14 ft	OPT
INSULATION - CEILING - CLOSED CELL - R-13 • (1) LAYER 1" CLOSED CELL FOAM INSULATION BETWEEN ROOF CROSS MEMBERS (R-5.5) • 1" CLOSED CELL FOAM INSULATION INSTALLED OVER TOP OF ROOF CROSS MEMBERS (R-6.5) • 3/8" PLYWOOD INSTALLED OVER TOP OF SECOND LAYER (R-1) • INTERIOR CEILING INSTALLED OVER TOP OF 3/8" PLYWOOD	14 ft	OPT
INTERIOR WALLS - WHITE VINYL WITH H-MOLDING	14 ft	OPT
INSULATION - WALLS - CLOSED CELL - R-13 • (1) LAYER 1" CLOSED CELL FOAM INSULATION BETWEEN WALL CROSS MEMBERS (R-5.5) • 1" CLOSED CELL FOAM INSULATION INSTALLED OVER TOP OF WALL CROSS MEMBERS (R-6.5) • 3/8" PLYWOOD INSTALLED OVER TOP OF SECOND LAYER (R-1) • INTERIOR COVERING INSTALLED OVER TOP OF 3/8" PLYWOOD	14 ft	OPT
FLOORING - TPO - BLACK COIN	14 ft	OPT
INSULATION - FLOOR - EXPANSION - 2" - R-14	14 ft	OPT
FIRE EXTINGUISHER - 2.5# BC	1 ea	OPT

SMOKE DETECTOR	1 ea	OPT
E-TRACK - SURFACE MOUNT - WALL	24 ft	OPT
ELECTRICAL		
BATTERY - 12V AGM (930 CA, 775 CCA)	1 ea	OPT
CONVERTER - 55 AMP WITH BATTERY CHARGER	1 ea	OPT
LIGHT - CLEARANCE - LED - 12V - AMBER - LOWER	2 ea	STD
LIGHT - CLEARANCE - LED - 12V - AMBER - UPPER	5 ea	STD
LIGHT - CLEARANCE - LED - 12V - RED - LOWER	2 ea	STD
LIGHT - CLEARANCE - LED - 12V - RED - UPPER	5 ea	STD
LIGHT - TAILLIGHT - SLIMLINE - LED - 12V - RED	1 pr	STD
RECEPT - INTERIOR - 120V - 15A - DEDICATED	3 ea	OPT
• GFCI PROTECTED WHERE REQUIRED BY CODE		
RECEPT - INTERIOR - 120V - 20A - DEDICATED	6 ea	OPT
• GFCI PROTECTED WHERE REQUIRED BY CODE		
RECEPT - EXTERIOR - 120V - 20A - GFI PROTECTED	1 ea	OPT
LIGHT - RECTANGULAR - LED - 18" - 12V - RECESSED - W/ TRIM RING	5 ea	OPT
SWITCH - WALL - 12V	2 ea	OPT
• USED FOR: LIGHT - RECTANGULAR - LED - 18" - 12V - RECESSED - W/ TRIM RING		
HEATING & AIR CONDITIONING		
HEATER - WALL MOUNT - 120V - 1500W - 5120 BTU - ELECTRIC - CHROME GRILL	1 ea	OPT
DEALER CUSTOM OPTIONS		
DEALER SUPPLIED WEIGHT DISTRIBUTION SET	1 ea	
FACTORY ADJUSTMENT FOR FRAMING CUSTOM RAMP DOOR	1 ea	
ATC CUSTOM OPTIONS		
A/C COMPARTMENT - WALL-MOUNT - EXTERIOR - COLOR MATCH - MINI SPLIT SYSTEM	1 ea	
• INCLUDES TOP-HINGED BAGGAGE DOOR W/ FL LATCH, LOUVERED VENT + GAS SHOCKS		
• INCLUDES VENTS ON SIDES		
• *** NOT TO BE INSTALLED ON TONGUE ***		
• *** NO INTERIOR LINER ***		
• EXPANDED METAL ON FLOOR OF COMPARTMENT		
A/C W/ HEAT PUMP - LG - MEGA - 1 TON SINGLE ZONE - 12,000 BTU - WALL MOUNT - 115V - WHITE	1 ea	
• HANDHELD WIRELESS REMOTE CONTROL		
• OPERATING EXT-TEMP RANGE; COOLING (14 TO 118 DEG F), HEATING (14 TO 65 DEG F)		
• WIREMOLD RACEWAY FOR PLUMBING RUNS		
• *** ONE DRAIN LINE PER WALL UNIT ***		
• *** UNIT MUST BE WITHIN 3 DEGS OF LEVEL ***		
• REQUIRES COMPARTMENT		
• ON 20AMP DEDICATED CIRCUIT, 120V		
• MAXIMUM TRAILER LENGTH OF 24' RECOMMENDED		
BREAKER BOX - 60 AMP SERVICE - 120/240V SINGLE PHASE - (120A @ 120V & 60A @ 240V)	1 ea	
• ***MOTORBASE AND SHORE CORD NOT INCLUDED***		
• 12 SPACE, 24 CIRCUIT PANEL		
CABINET - ALUMINUM - LOWER - 24"W X 30"H X 24"D	1 ea	
CABINET - ALUMINUM - LOWER - STRAIGHT - 24"W X 30"H - W/ 24"W 5-DRAWER UNIT	1 ea	
COUNTERTOP - ALUMINUM - FIXED - 24" DEEP	6 ft	
DOOR - ENTRANCE - 405 SERIES - 30" X 78" - FLUSH LOCK	1 ea	
• LEFT HINGE		
DOOR - REAR RAMP - CABLELESS - 40"W - 2000# RATED	1 ea	
POWER INLET - APPLETON - ADJA6033-125-RS, 480V 60 AMP, SINGLE PHASE, CONNECTED TO TRANSFORMER	1 ea	
• ***SHORE CORD NOT INCLUDED***		
PVC - 3" - PASS THROUGH	2 ea	
• SCREW IN CAPS ON INTERIOR AND EXTERIOR		

TRANSFORMER - 15KVA - 480V SINGLE PHASE TO 120/240V SINGLE PHASE - INSTALLED BETWEEN 480V SINGLE
PHASE POWER INLET TO 120/240V 60 AMP SERVICE

1 ea

- 60A MAIN BREAKER INSTALLED BETWEEN 480V SINGLE PHASE POWER INLET AND TRANSFORMER