



110 East North Avenue, Carol Stream, IL 60188 Toll Free 800-832-5331 ph. (630) 580-5840 fx (630) 580-5843

## 2017 MTI 8.5' Wide Round Top Cargo Trailer

Model	Description
8.5X24TA2	8.5 x 24 TA2 MST (Spring Axle) VIN: ...HM639682 Exterior Color: White

SELECTED OPTIONS			
Option Code	Description	Unit of Measure	Quantity
6.10	Stabilizer Jacks (Medium Duty) 1000 lb. - Crank Down	pr.	2
6.24	Additional Floor Crossmembers for 16" On Center	ea.	6
17.07	Add 6 in height [8' and 8.5' Wide Units ]	LF	24
18.01	Electrical Package #1	ea.	1
	(2) Fluorescents 4' or 8'		
	(1) 110-Volt Switch		
	(2) 110-Volt Interior Recepts		
	30 Amp. Service with Life Line		
11.07	Motor Base Plug - 30 Amp. (Must have an Electric Panel)	ea.	1
	This is a plug on the outside of the trailer for power supply like an RV (Lifeline Option is simply a cord that drops from the floor of the trailer)		
10.02	Solid Awning Doors - Over 32 sq. ft.	sq. ft.	110
	Flip up doors are 5' x 11' (110 sq. ft. total)		
2.06	Upgrade Interior Walls to 3/8" Plywood IPO Luan	ft.	24
11.29	110-Volt Duplex Recept - Interior - 20 Amp	ea.	3

1. There will be double cargo doors on the rear
2. There will be two flip up windows 5' x 12' just above the wheel well and just under the top of the trailer
3. Two of the regular 15 amp and three of the 20 amp outlets
4. Client requested two 8' fluorescent lights
5. Interior height will be 7'

\*\*\* Custom sizes and configurations available on request. \*\*\*

Specifications and Pricing subject to change without notice.



# MIDDLEBURY TRAILERS

## MST Series

5', 6', & 7' Wides  
Round Top  
Cargo Trailer



MST Shown with Options:  
Two-Tone Metal  
Brite Aluminum Corners

### STANDARD FEATURES & SPECIFICATIONS

#### Hitch

2-5/16" Coupler with Safety Chains - Tandem Axles  
2,000 lb. Top Wind Jack w\Sand Pad

#### Axle

MST = Spring Axles

Brake Axles on SAE and Tandem Axle Models

#### Tires and Rims

"D" = Bias-Ply Tires, "R" = Radial Tires

##### MST

3,000 lb. Axle	ST205/75D15	
3,500 lb. Axle	ST205/75D15	ST205/75R15
5,200 lb. Axle	ST225/75R15	

White Wheels Standard on MST and MTT Models

#### Frame

All Frames are Undercoated

	Floor	Walls	Roof
MST 5', 6', & 7' Wides	24" o.c.	24" o.c.	24" o.c.
All 8.5' Wides	24" o.c.	16" o.c.	24" o.c.
All TA3 Axles	16" o.c.	16" o.c.	24" o.c.

#### Side Door

8.5' Wide, 18' & Above -- 48" Camlock Door & No Step\*

#### Rear Doors

Width	Single Door	Double Door	Ramp Door
5'	X	X	Light Duty
6'		X	Light Duty
7'		X	Light Duty
8.5'		X	

\* Light Duty Ramp Door has a 1,000 lb. capacity

#### Interior

3/4" Engineered Wood Flooring  
MST - Luan Walls, Trimmed with Luan

#### Interior Heights

8.5' Wides - 6' 6"

#### Exterior

.030 Exterior Metal  
Fiberglass Cap  
24" ATP Stoneguard  
Galvanized Steel Roof  
Aluminum Fenders

3" Lower Trim

#### Electrical

Breakaway Box, Battery, & Switch On Electric Brake Axles  
(2) 12-Volt Dome Lights With Switch  
7-Way Plug on Electric Brake Axles  
4-Way Plug on Idler Axles  
LED Strip Tail Light/Brake Lights, Surface Mounted  
LED Surface Mounted Clearance Lights