

2010 Wells Cargo – Gooseneck Trailer

Model: CVG2825W

14,700# GVWR

6,000# GAWR

8.5 wide Standard Equipment

- .030 Aluminum Exterior
- 12 Volt Interior Wall Switch
- 2-5/16in 25,000lb Ball Coupler - Round.
- 3/8" PlexCore Sidewall Liner.
- 6'6" Inside Height
- DOT Conspicuity Tape on Side & Rear of Trailer
- Max Size Double Rear Doors/Steel Strap Hinges
- S.A.E. Color Coded 12 Volt Electrical System
- Smooth Aluminum Fenderettes
- Torflex Suspension
- 102" Wide Track
- 12 Volt LED Dome Light (Requires 12v Wall Switch)
- 3/4in PlexCore Decking.
- 36 x 66 Radius Side PT Door - RH Hinge.
- Bonded Aluminum <= 7 Feet
- Crossmembers 24in On Center
- Electric Drum Brakes (DOT Batt & Breakaway Req'd)
- One Piece Aluminum Roof
- Seven Way Trailer End Connector
- Tandem Manual 2-Speed Landing Gear Assembly
- Vertical Posts 16in On Center

Options:

- Rear Ramp Door
- 12 kW On-Board Onan Generator
 - Running Hours: 3,446
- Exterior Lighting on All Sides
- Powered Curb Side Awning
 - Includes a Wind Sensing Awning Controller
- Storage in Bunk Area
- Cold Strip Curtain Across Rear Door Opening
- Cold Strip Curtain Across Side Door Opening
- 2 Roof Mounted Air Conditioning Units
- Cabinets on Front Wall
- Additional 24 inches of Interior Height
 - Interior Height Upgraded to 8' 6"
- Black Coin Flooring
- Black Coin Ramp
- Three Fluorescent Lights w/Diffusers
- Equalizer Systems Dual Leg Hydraulic Tongue Jack System
- Exterior Outlets