

Centrifugal dryers

Technical specifications

Easy Access Dryer

Easy Access Models: The noise level of an Easy Access Dryer is 95 dBA or less at 1 meter processing 3 mm diameter x 3 mm long LDPE pellets and the buyer insulating the pellet outlet and air outlet lines. This can be reduced to 87 dBA or less with optional low-noise modifications. **(Please note that larger and/or harder pellets will adversely affect the noise level.)**



Model 3032DW Easy Access



Model 100 High-Capacity Dryer

Model	Drying Capacity (lbs/hr)	Max. BF (GPM) Water Rate	Max. DW (GPM) Water Rate	Air Flow (CFM)	Motor Size (HP)
1008	500 kg/h (1,100)	12 m³/h (50)	N/A	510 Nm³/h (300)	2.2 kW (3)
2008	1,200 kg/h (2,600)	20 m³/h (90)	N/A	680 Nm³/h (400)	4 kW (5)
2016	2,500 kg/h (5,500)	50 m³/h (220)	70 m³/h (300)	1,700 Nm³/h (1,000)	4 kW (5)
3016	6,500 kg/h (14,000)	70 m³/h (300)	100 m³/h (440)	2,720 Nm³/h (1,600)	5.5 kW (7.5)
4016	8,200 kg/h (18,000)	70 m³/h (300)	100 m³/h (440)	3,400 Nm³/h (2,000)	5.5 kW (7.5)
3032	11,500 kg/h (25,000)	45 m³/h (200)	180 m³/h (800)	5,100 Nm³/h (3,000)	7.5 kW (10)
4032	18,500 kg/h (41,000)	45 m³/h (200)	340 m³/h (1,500)	6,800 Nm³/h (4,000)	11 kW (15)
5032	26,000 kg/h (57,000)	45 m³/h (200)	340 m³/h (1,500)	8,500 Nm³/h (5,000)	15 kW (20)
5048	40,000 kg/h (88,000)	90 m³/h (400)	685 m³/h (3,000)	12,750 Nm³/h (7,500)	22 kW (30)
6048	50,000 kg/h (110,000)	90 m³/h (400)	685 m³/h (3,000)	15,300 Nm³/h (9,000)	30 kW (40)
7048	85,000 kg/h (187,000)	90 m³/h (400)	910 m³/h (4,000)	21,875 Nm³/h (12,500)	55 kW (75)

Specifications are subject to change without notice when products are improved in quality or performance.

High-Capacity Dryer

Model	Drying Capacity (lbs/hr)	Max. BF (GPM) Water Rate	Max. DW (GPM) Water Rate	Air Flow (CFM)	Motor Size (HP)
60	60,000 kg/h (130,000)	90 m³/h (400)	685 m³/h (3,000)	18,700 Nm³/h (11,000)	55 kW (75)
70	70,000 kg/h (150,000)	90 m³/h (400)	910 m³/h (4,000)	18,700 Nm³/h (11,000)	55 kW (75)
100	100,000 kg/h (220,000)	90 m³/h (400)	1,360 m³/h (6,000)	21,875 Nm³/h (12,800)	90 kW (120)

Specifications are subject to change without notice when products are improved in quality or performance.