

## Safety Data Sheet acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

### 1 Identification

- **Product identifier**
- **Trade name: 6001H**
- **Application of the substance / the mixture** Accelerator
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Cyberbond LLC  
401 North Raddant Road  
Batavia, IL 60510  
USA  
sales@cyberbond1.com  
630-761-8900
- **Information department:** Product safety department
- **Emergency telephone number:**  
International-1-(352)-323-3500  
US & Canada-1-(800)-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Harmful

Harmful by inhalation, in contact with skin and if swallowed. Harmful: may cause lung damage if swallowed.



Irritant

Irritating to eyes.



Highly flammable

Highly flammable.

Danger of cumulative effects.

- **Information concerning particular hazards for human and environment:**

The product has to be labeled due to the calculation procedure of international guidelines.

(Contd. on page 2)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: 6001H

(Contd. of page 1)

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02

GHS07

GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Petroleum Distillates  
acetone  
N,N-dimethyl-p-toluidine

- **Hazard statements**

Highly flammable liquid and vapor.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.  
May be fatal if swallowed and enters airways.

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wear protective gloves / eye protection / face protection.  
Wear eye protection / face protection.  
Ground/bond container and receiving equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
If swallowed: Immediately call a poison center/doctor.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
Call a poison center/doctor if you feel unwell.  
If eye irritation persists: Get medical advice/attention.  
Get medical advice/attention if you feel unwell.  
Do NOT induce vomiting.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store locked up.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: 6001H

(Contd. of page 2)

· <b>Dangerous components:</b>		
68410-97-9	Petroleum Distillates	50-100%
67-64-1	acetone	25-50%
99-97-8	N,N-dimethyl-p-toluidine	1-≤2.5%

## 4 First-aid measures

### · **Description of first aid measures**

#### · **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

#### · **After swallowing:**

If symptoms persist consult doctor.

Immediately call a doctor.

#### · **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** Breathing difficulty

#### · **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Fire-fighting measures

### · **Extinguishing media**

· **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

### · **Advice for firefighters**

#### · **Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

## 6 Accidental release measures

### · **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

#### · **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

#### · **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

#### · **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

### · **Handling:**

#### · **Precautions for safe handling**

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

#### · **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: 6001H

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Store only in the original receptacle.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

### Components with limit values that require monitoring at the workplace:

#### 67-64-1 acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m <sup>3</sup> , (500) NIC-250 ppm BEI

#### 99-97-8 N,N-dimethyl-p-toluidine

WEEL	Long-term value: 0.5 ppm
------	--------------------------

### Ingredients with biological limit values:

#### 67-64-1 acetone

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.

### Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.

- **Breathing equipment:** Not necessary if room is well-ventilated.

#### Protection of hands:



Protective gloves

#### Impervious gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves** Nitrile rubber, NBR

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Not suitable are gloves made of the following materials:**

Cotton or natural fibers  
PVC gloves

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: 6001H

(Contd. of page 4)

- **Eye protection:**

Safety glasses



Tightly sealed goggles

- **Body protection:** Protective work clothing

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:** Liquid

- **Color:** Colorless

- **Odor:** Like aromatic solvents

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

- **Melting point/Melting range:** Undetermined.

- **Boiling point/Boiling range:** 56 °C (133 °F)

- **Flash point:** -20 °C (-4 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 465 °C (869 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

- **Lower:** 2.6 Vol %

- **Upper:** 13.0 Vol %

- **Vapor pressure at 20 °C (68 °F):** 233 hPa (175 mm Hg)

- **Density at 20 °C (68 °F):** 0.732 g/cm<sup>3</sup> (6.109 lbs/gal)

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

- **Water:** Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

- **Dynamic:** Not determined.

- **Kinematic:** Not determined.

- **Solvent content:**

- **Organic solvents:** 27.0 %

- **VOC content:** 197.6 g/l / 1.65 lb/gl

- **Other information** No further relevant information available.

(Contd. on page 6)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: 6001H

(Contd. of page 5)

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant
- **Carcinogenic categories**

<b>· IARC (International Agency for Research on Cancer)</b>
---

None of the ingredients is listed.
------------------------------------

<b>· NTP (National Toxicology Program)</b>
--

None of the ingredients is listed.
------------------------------------

<b>· OSHA-Ca (Occupational Safety &amp; Health Administration)</b>
--

None of the ingredients is listed.
------------------------------------

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: 6001H

(Contd. of page 6)

## 14 Transport information

- UN-Number
- DOT, IMDG, IATA
- UN proper shipping name
- DOT
- IMDG, IATA
- Transport hazard class(es)
- DOT

UN1993  
 Flammable liquids, n.o.s. (Acetone, Petroleum Distillates)  
 FLAMMABLE LIQUID, N.O.S. (ACETONE, Petroleum Distillates)



- Class
- Label

3 Flammable liquids  
 3

- IMDG, IATA



- Class
- Label
- Packing group
- DOT, IMDG, IATA
- Environmental hazards:
- Marine pollutant:
- Special precautions for user
- Danger code (Kemler):
- EMS Number:
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
- Transport/Additional information:
- DOT
- Quantity limitations

3 Flammable liquids  
 3  
 II  
 No  
 Warning: Flammable liquids  
 33  
 F-E,S-E  
 Not applicable.

On passenger aircraft/rail: 5 L  
 On cargo aircraft only: 60 L

- IMDG

- Limited quantities (LQ)
- Excepted quantities (EQ)

1L  
 Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml

- UN "Model Regulation": UN1993, Flammable liquids, n.o.s. (Acetone, Petroleum Distillates), 3, II

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

### TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: 6001H

(Contd. of page 7)

· **Proposition 65**

· <b>Chemicals known to cause cancer:</b>	
99-97-8	N,N-dimethyl-p-toluidine
· <b>Chemicals known to cause reproductive toxicity for females:</b>	
None of the ingredients is listed.	
· <b>Chemicals known to cause reproductive toxicity for males:</b>	
None of the ingredients is listed.	
· <b>Chemicals known to cause developmental toxicity:</b>	
None of the ingredients is listed.	

· **Carcinogenic categories**

· <b>EPA (Environmental Protection Agency)</b>		
67-64-1	acetone	I
· <b>TLV (Threshold Limit Value established by ACGIH)</b>		
67-64-1	acetone	A4
· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
None of the ingredients is listed.		

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

Petroleum Distillates  
acetone  
N,N-dimethyl-p-toluidine

· **Hazard statements**

Highly flammable liquid and vapor.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.  
May be fatal if swallowed and enters airways.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wear protective gloves / eye protection / face protection.  
Wear eye protection / face protection.  
Ground/bond container and receiving equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
If swallowed: Immediately call a poison center/doctor.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
Call a poison center/doctor if you feel unwell.  
If eye irritation persists: Get medical advice/attention.  
Get medical advice/attention if you feel unwell.

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

**Trade name: 6001H**

(Contd. of page 8)

Do NOT induce vomiting.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product Safety Department

· **Contact:** Cyberbond Regulatory Department

· **Date of preparation / last revision** 06/02/2015 / 3

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1